

magnetic[®] basic mobil mini

mobile filling station

Description:

Refillable, mobile filling station with an electrical conductivity (μS) measuring/monitoring device, a resettable digital water quantity counter at the outlet to the system and a rugged carrying handle. For safe and simple demineralization of filling water for closed-circuit heating/cooling systems, uses the continuous-flow method and an ion exchange basis with mixed bed resin in accordance with VDI 2035. Resin container made of fibre-reinforced plastic fabric. Screw-off filling head for a simple on-site resin replacement.

Technical Data: magnetic[®] basic mobil mini

Capacity at german hardness (°dH)	
1 °dH	10,000 litres
10 °dH	1,000 litres

Capacity at french hardness (°fH)	
1 °fH	17,800 litres
10 °fH	1,780 litres

- ⇒ Filling quantity 6,5 litres premium mixed bed resin
- ⇒ Max. flow rate: 420 litres/h at 3-4 bar supply pressure
- ⇒ Max. filling temperature: 60 °C
- ⇒ Max. filling pressure: 6 bar
- ⇒ Threaded coupling: 2x DN 20 3/4"
- ⇒ Total height: 710 mm
- ⇒ Weight (ready for work) 9 kg

Manufacturer / Supplier:

magnetic GmbH & Co. KG
Am Richtbach 5
74547 Untermuenkheim, Germany
Tel.: +49 (0)7944 94199-0
Fax: +49 (0)7944 94199-19
www.magnetic-online.de
info@magnetic-online.de



magnetic[®] ...einfach besser